## SKM IR 2 MULTI Q

Square multi-coupling (fixed)



| Properties        |   |  |  |
|-------------------|---|--|--|
| Application       | Industry<br>Transport and municipal vehicles<br>Agricultural technology |  |  |
| Connection 1      | BSP cylindrical internal threads  |  |  |
| Connection 2      | Plug in sleeve  |  |  |
| Design            | Multicoupling   |  |  |
| Construction type | Panel construction as quick-change system                               |  |  |
| max: Flow         | 40 L/min  |  |  |



## Description

Quick release couplings are used when add-on parts need to be replaced frequently.

## Additional information

Multi couplings offer considerable benefits

over bundled screw and plug-in couplings:

- Time saving factor due to fast and convenient exchange of add-on parts
- Convenient handling with simultaneous coupling of multiple connections
- Trouble-free coupling even if system pressures are applied
- No confusion between connections, no reversal of flow paths
- Flat seal valves prevent oil leakages, air admittance and allows efficient cleaning even in soiled working environments

| ILCIII              |                   |                    |  |
|---------------------|-------------------|--------------------|--|
| Identification      | Connecting thread | Operating pressure |  |
|                     |                   | (bar)              |  |
| SKM 13 IR 2 MULTI Q | G 1/2" -14        | 250,0              |  |