

# HK FMP

Housing for pressure filter FMP 320 bar

**HANSA FLEX**

## Properties

<b>Design</b>	without bypass valve, without clogging indicator without filter element
<b>Operating pressure</b>	max. 320 bar



## Note

Measurement "B": clearance required for changing the filter element

## Description

Pressure filter for pipeline installation

Design (Qmax.) for medium ISO VG 46 at 50°C (30 mm<sup>2</sup>/s) at  $\Delta p_{tot} = 1.25$  bar

## Ordering information

Filter element is not included. Please order separately.

## Item

Identification	Filter area (m <sup>2</sup> )	Line connection	B (mm)	A (mm)	C (mm)	D (mm)	Ø E (mm)	Weight (kg)
HK FMP 065 1 SG1	374	G 1/2"	100	169	28	85	68	3,9
HK FMP 065 2 SG2	530	G 3/4"	100	200	28	85	68	4,2
HK FMP 065 3 SG2	1064	G 3/4"	100	302	28	85	68	5,7
HK FMP 135 2 SG2	2020	G 1"	125	333	38	104	77	9,4

## Accessories

HK VA OPT	Clogging indicator optical
HK VA EL	Clogging indicator electrical

## Spare parts

HK HP H	Filter element for pressure filter FMP/FHP
---------	--