

Properties			
Connection 1	Coupling female connection		
Sealing form 1	O-ring seal		
Connection 2	BSP cylindrical external threads		
Material	Steel		
Surface	hot galvanised		



Item				
Identification	Operating pressure	Coupling dimension	G1	
	(bar)	(mm)		
PRT M 50 HR 1.1/2	12,0	50,0	G 1.1/2" -11	
PRT M 50 HR 2	12,0	50,0	G 2"	
PRT M 50 HR 2.1/2	12,0	50,0	G 2.1/2" -11	
PRT M 70 HR 2	12,0	70,0	G 2"	
PRT M 70 HR 2.1/2	12,0	70,0	G 2.1/2" -11	
PRT M 70 HR 3	12,0	70,0	G 3" -11	
PRT M 89 HR 2.1/2	12,0	89,0	G 2.1/2" -11	
PRT M 89 HR 3	12,0	89,0	G 3" -11	
PRT M 108 HR 2.1/2	12,0	108,0	G 2.1/2" -11	
PRT M 108 HR 3	12,0	108,0	G 3" -11	
PRT M 108 HR 4	12,0	108,0	G 4" -11	
PRT M 133 HR 2.1/2	12,0	133,0	G 2.1/2" -11	
PRT M 133 HR 4	12,0	133,0	G 4" -11	
PRT M 133 HR 5	12,0	133,0	G 5" -11	
PRT M 159 HR 2.1/2	12,0	159,0	G 2.1/2" -11	
PRT M 159 HR 4	12,0	159,0	G 4" -11	
PRT M 159 HR 6	12,0	159,0	G 6" -11	