

PRT M HR

Perrot coupling female part, external thread

HANSA FLEX

Properties

Connection 1 Coupling female connection

Sealing form 1 O-ring seal

Connection 2 BSP cylindrical external threads

Material Steel

Surface hot galvanised



Item			
Identification	Operating pressure (bar)	Coupling dimension (mm)	G1
PRT M 50 HR 1.1/2	12,0	50,0	G 1.1/2" -11
PRT M 50 HR 2	12,0	50,0	G 2"
PRT M 50 HR 2.1/2	12,0	50,0	G 2.1/2" -11
PRT M 70 HR 2	12,0	70,0	G 2"
PRT M 70 HR 2.1/2	12,0	70,0	G 2.1/2" -11
PRT M 70 HR 3	12,0	70,0	G 3" -11
PRT M 89 HR 2.1/2	12,0	89,0	G 2.1/2" -11
PRT M 89 HR 3	12,0	89,0	G 3" -11
PRT M 108 HR 2.1/2	12,0	108,0	G 2.1/2" -11
PRT M 108 HR 3	12,0	108,0	G 3" -11
PRT M 108 HR 4	12,0	108,0	G 4" -11
PRT M 133 HR 2.1/2	12,0	133,0	G 2.1/2" -11
PRT M 133 HR 4	12,0	133,0	G 4" -11
PRT M 133 HR 5	12,0	133,0	G 5" -11
PRT M 159 HR 2.1/2	12,0	159,0	G 2.1/2" -11
PRT M 159 HR 4	12,0	159,0	G 4" -11
PRT M 159 HR 6	12,0	159,0	G 6" -11