


Properties			
Application	Connection fitting for metal hoses		
Connection 1	imperial internal thread, cylindrical		
Sealing form 1	flat sealing		
Standard	DIN EN 10226 / ISO 7-1		
Construction	straight		
Application	soldered variant temperature resistant up to 200 °C		
Material	Malleable cast iron		





Note

Width across flats values are listed for reference purposes!

The specified working pressure PN(bar) relates to the working temperature of -20 $^{\circ}$ C to 120 $^{\circ}$ C. At working temperature of 120 $^{\circ}$ C to 200 $^{\circ}$ C the working pressure PN (bar) reduces to 22,7 bar.

Ordering information

Other designs available on request

Item				
Identification	DN	PN (bar)	G1	S1 (mm)
WA 006 VBF	6	25	Rp 1/4"	28,0
WA 010 VBF	10	25	Rp 3/8"	32,0
WA 013 VBF	13	25	Rp 1/2"	39,0
WA 020 VBF	20	25	Rp 3/4"	48,0
WA 025 VBF	25	25	Rp 1"	55,0
WA 032 VBF	32	25	Rp 1.1/4"	67,0
WA 040 VBF	40	25	Rp 1.1/2"	74,0
WA 050 VBF	50	25	Rp 2"	90,0
WA 065 VBF	65	25	Rp 2.1/2"	111,0
WA 080 VBF	80	25	Rp 3"	130,0

Product versions		
WA VBF RG	Connector VBF, red bronze, Red bronze	
WA VBF VA	Connector VBF, VA, Stainless steel	