HK PAM 015 T

Manual pump for tank installation with directional control valve

HANSA-FLEX

Properties

Scope of supply	incl. seal and screw set
Material	Housing: cast iron, inner parts steel





Note

The pressure relief valves must be set according to the application.

Ordering information

Caution! Remember to order the hand lever HKPAM0290000!

Item

Identification	Thread	Vdh (ccm) (cc)	Design	p max. (bar)	Pressure (30)* (bar)	Weight (kg)
HK PAM 015 1200	2 x 3/8" AG	12	with 4/3-way valve	380	160	2,85
HK PAM 015 1202	2 x 3/8" AG	12	with pressure relief valve and 4/3-way valve	380	160	3,00
HK PAM 015 2500	2 x 3/8" AG	25	with 4/3-way valve	350	100	2,95
HK PAM 015 2502	2 x 3/8" AG	25	with pressure relief valve and 4/3-way valve	350	100	3,10
HK PAM 015 4500	2 x 3/8" AG	45	with 4/3-way valve	280	80	3,15
HK PAM 015 4502	2 x 3/8" AG	45	with pressure relief valve and 4/3-way valve	280	80	3,30

Vdh = conveying volume per double stroke – Pressure (30)= pressure with hand force 30 daN with standard lever

Accessories

HK PAM Hebel	Lever for PAM manual pump
HK PM0 022	Tank for PAM manual pump
HK PAM Faltenbalg	Bellows for PAM manual pump

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.