

# HK RZMO AE 030

Proportional pressure relief valve size 6

**HANSA FLEX**

## Properties

|                           |   |
|---------------------------|---|
| <b>Design</b>             | Proportional plate mounting valve<br>pilot-controlled |
| <b>Scope of supply</b>    | with integrated electronics<br>without plug           |
| <b>Operating pressure</b> | max. 315 bar  |
| <b>Volumetric flow</b>    | max. 40 l/min   |
| <b>Connection</b>         | ISO/Cetop 03 size 6                                   |



## Description

with integrated electronics  
Response time < 60 ms  
Hysteresis < 1,5%  
Pilot signal 0-10 VDC

## Item

| Identification     | acts in channel | Pressure setting range<br>min.<br>(bar) | Pressure setting range<br>max.<br>(bar) | Volumetric flow<br>min.<br>(L/min) | Volumetric flow<br>max.<br>(L/min) | Weight<br>(kg) |
|--------------------|-----------------|---|---|------------------------------------|------------------------------------|----------------|
| HK RZMO AE 030 210 | P               | 6                                       | 210                                     | 2,5                                | 40,0                               | 2,8            |
| HK RZMO AE 030 315 | P               | 6                                       | 315                                     | 2,5                                | 40,0                               | 2,8            |

## Accessories

|            |  |
|------------|--|
| HK SPZ     | Electrical connector for proportional valves |
| HK M HK DH | Screw set for NG 6 valves type HK DH / DG4V3 |