

HK M HK DH

Screw set for NG 6 valves type HK DH / DG4V3

Properties

Design	Hexagon socket screw
Standard	DIN 912-12.9



Item				
Identification	for valve type	Tightening torque (N-m)	Scope of supply	Weight (kg)
HK M5 30	1 directional control valve	8,3		0,03
HK M5 50	1 control valve HK DHI	8,3	4 No. M5 x 50	0,05
HK M5 70	1 directional control valve + 1 sandwich body valve	8,3		0,06
HK M5 90	1 control valve HK DHI + 1 sandwich body valve	8,3	4 No. M5 x 90	0,09
HK M5 110	1 directional control valve + 2 sandwich body valves	8,3		0,09
HK M5 130	1 control valve HK DHI + 2 sandwich body valves	8,3	4 No. M5 x 130	0,10
HK M5 150	1 directional control valve + 3 sandwich body valves	8,3		0,11
HK M5 170	1 control valve HK DHI + 3 sandwich body valves	8,3	4 No. M5 x 170	0,12

Accessory for following products

HK DH01	Hand-operated directional control valve NG6
HK DH04/05	Directional control valve NG6, hydraulically controlled
HK DH08/09	Directional control valve NG6, pneumatically controlled
HK DHA	Solenoid-operated directional control valve size 6, Ex-protected
HK DHE X 00 DC	Solenoid-operated directional control valve size 6 without coil
HK DHE X 00 AC	Solenoid-operated directional control valve size 6 without coil
HK DHQ	High speed/creep speed unit for flow control valve QV
HK DHZO A	Proportional solenoid-operated directional control valve size 6
HK DLO	Poppet valve NG6
HK DLHZO TE	Proportional solenoid-operated directional control valve size 6
HK DG4V3	Solenoid-operated directional control valve NG6