HK M HK 41 C

Set of bolts for NG6 valves type HK 41C

Properties

Design	Hexagon socket screw
Standard	DIN 912-12.9



Item

Identification	for valve type	Tightening torque (N-m)	Scope of supply	Weight (kg)
HK M5 30	1 directional control valve	8,3		0,03
HK M5 60	1 directional control valve + 1 sandwich body valve (ZRV)	8,3		0,05
HK M5 70	1 directional control valve + 1 sandwich body valve	8,3		0,06
HK M5 80	1 directional control valve + 1 sandwich body valve (ZRV-AB)	8,3		0,07
HK M5 100	1 directional control valve + 2 sandwich body valves (with 1 x ZRV)	8,3		0,08
HK M5 110	1 directional control valve + 2 sandwich body valves	8,3		0,09
HK M5 120	1 directional control valve + 2 sandwich body valves (with 1 x ZRE-AB)	8,3		0,09
HK M5 140	1 directional control valve + 3 sandwich body valves (with 1 x ZRV)	8,3		0,10
HK M5 150	1 directional control valve + 3 sandwich body valves	8,3		0,11
HK M5 160	1 directional control valve + 3 sandwich body valves (with 1 x ZRE-AB)	8,3		0,12

Accessory for following products

HK 41 C1	Hand-operated directional control valve NG6
HK 41 C1 (7/G/Q/R)	Solenoid-operated directional control valve NG6

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.