

HK M HK DK

Set of bolts for NG 10 valves types HK DK11/DKE/DG4V5

Properties

| | |
|-----------------|----------------------|
| Design | Hexagon socket screw |
| Standard | DIN 912-12.9 |



| Item | | | | |
|----------------|--|----------------------------|-----------------|----------------|
| Identification | for valve type | Tightening torque (N·m) | Scope of supply | Weight (kg) |
| HK M6 40 | 1 directional control valve | 14,0 | | 0,06 |
| HK M6 90 | 1 directional control valve + 1 sandwich body valve | 14,0 | | 0,10 |
| HK M6 140 | 1 directional control valve + 2 sandwich body valves | 14,0 | | 0,12 |
| HK M6 190 | 1 directional control valve + 3 sandwich body valves | 14,0 | | 0,20 |

Accessory for following products

| | |
|----------------|--|
| HK DK11 | Hand-operated directional control valve NG10 |
| HK DKE X 00 DC | Solenoid-operated directional control valve size10 without coil |
| HK DKE X 00 AC | Solenoid-operated directional control valve size10 without coil |
| HK DKZOR A | Proportional solenoid-operated directional control valve size 10 |
| HK DLKZOR TE | Proportional solenoid-operated directional control valve size 10 |
| HK DG4V5 | Solenoid-operated directional control valve NG10 |