# HK M HK 42 C

Set of bolts for NG10 valves type HK 42 C

## Properties

| | |
|---|---|
| **Design** | Hexagon socket screw |
| **Standard** | DIN 912-12.9 |



## Item

| Identification | for valve type | Tightening torque (N-m) | Scope of supply | Weight (kg) |
|---|---|---|---|---|
| **HK M6 40** | 1 directional control valve | 14,0 | | 0,06 |
| **HK M6 75** | 1 directional control valve + 1 sandwich body valve (ZRV) | 14,0 | | 0,08 |
| **HK M6 90** | 1 directional control valve + 1 sandwich body valve | 14,0 | | 0,10 |
| **HK M6 125** | 1 directional control valve + 2 sandwich body valves (with 1 x ZRV) | 14,0 | | 0,11 |
| **HK M6 140** | 1 directional control valve + 2 sandwich body valves | 14,0 | | 0,12 |
| **HK M6 175** | 1 directional control valve + 3 sandwich body valves (with 1 x ZRV) | 14,0 | | 0,16 |
| **HK M6 190** | 1 directional control valve + 3 sandwich body valves | 14,0 | | 0,20 |

## Accessory for following products

| | |
|---|---|
| **HK 42 C1 (7/G/Q/R)** | Solenoid-operated directional control valve NG10 |

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*