Plug-in coupling connector



Properties	
Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Design	Snap-tite series 72
Connection 1	BSP cylindrical internal threads
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
Additional feature	ISO 7241-1 Series B
Material	Stainless steel



Description

Plug-in couplings allow quick coupling.

Ordering information

Other pressure and temperature figures available on request.

Item							
Identification	DN*	Connecting thread	Operating pressure	SF coup.*	Mineral oil temp. min.	Mineral oil temp. max.	
SKS 04 IR SN72 VA	5	G 1/8" -28	280,0	4	-25	200	
SKS 06 IR SN72 VA	6	G 1/4" -19	380,0	4	-25	200	
SKS 10 IR SN72 VA	10	G 3/8" -19	260,0	4	-25	200	
SKS 13 IR SN72 VA	12	G 1/2" -14	260,0	4	-25	200	
SKS 20 IR SN72 VA	19	G 3/4" -14	210,0	4	-25	200	
SKS 25 IR SN72 VA	25	G 1" -11	210.0	4	-25	200	

DN = Nominal diameter, nominal width - SF gek. = Safety factor coupled

Product versions

SKS IR SN72 Plug-in coupling connector, electro galvanised

Accessories

SKS ZUBS SN72 Dust protection coupling connector, SKS..SN 72