

# SKS IR SN72 VA

Plug-in coupling connector

## Properties

<b>Application</b>	General application, e.g. in industry, construction machinery, agricultural technology etc.
<b>Design</b>	Snap-tite series 72
<b>Connection 1</b>	BSP cylindrical internal threads
<b>Sealing form 1</b>	for screw-in pins with shapes A, B and if necessary E
<b>Additional feature</b>	ISO 7241-1 Series B
<b>Material</b>	Stainless steel



## Description

Plug-in couplings allow quick coupling.

## Ordering information

Other pressure and temperature figures available on request.

## Item

Identification	DN*	Connecting thread	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKS 04 IR SN72 VA	5	G 1/8" -28	280,0	4	-25	200
SKS 06 IR SN72 VA	6	G 1/4" -19	380,0	4	-25	200
SKS 10 IR SN72 VA	10	G 3/8" -19	260,0	4	-25	200
SKS 13 IR SN72 VA	12	G 1/2" -14	260,0	4	-25	200
SKS 20 IR SN72 VA	19	G 3/4" -14	210,0	4	-25	200
SKS 25 IR SN72 VA	25	G 1" -11	210,0	4	-25	200

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

## Product versions

SKS IR SN72 Plug-in coupling connector, electro galvanised

## Accessories

SKS ZUBS SN72 Dust protection coupling connector, SKS..SN 72