

Properties					
Application	General application, e.g. in industry, construction machinery, agricultural technology etc.				
Connection 1	BSP cylindrical internal threads				
Sealing form 1	for screw-in pins with shapes A, B and if necessary E				
compatible with	Stucchi				
Material	Stainless steel				



## Note

Interchangeable with couplings to ISO 16028.

## Description

For a high flow with minimal pressure loss.

Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.

Suitable for use in environmentally sensitive areas.

## Ordering information

Other pressure and temperature figures available on request.

Item							
Identification	DN*	Connecting thread	Size	Operating pressure (bar)	SF coup.*	Mineral oil temp. min.	Mineral oil temp. max.
SKM 06 IR 1 FS VA	6	G 1/4" -19	1	400,0	4	-25	200
SKM 10 IR 2 FS VA	10	G 3/8" -19	2	250,0	4	-25	200
SKM 13 IR 2 FS VA	12	G 1/2" -14	2	250,0	4	-25	200
SKM 13 IR 3 FS VA	12	G 1/2" -14	3	250,0	4	-25	200
SKM 20 IR 3 FS VA	19	G 3/4" -14	3	250,0	4	-25	200
SKM 20 IR 4 FS VA	19	G 3/4" -14	4	250,0	4	-25	200
SKM 25 IR 5 FS VA	25	G 1" -11	5	250,0	4	-25	200

 ${\sf DN = Nominal\ diameter,\ nominal\ width\ -\ SF\ gek. = Safety\ factor\ coupled}$ 

	 1 4	vers	!
_	шот	VARC	IANE

SKM IR FS Plug-in coupling sleeve, electro galvanised

## Accessories

SKM ZUBS FS Dust protection coupling sleeve, SKM..FS