SKM IR FS VA

Plug-in coupling sleeve

Properties

Application	General application, e.g. in industry, construction machinery, agricultural technology etc.
Connection 1	BSP cylindrical internal threads
Sealing form 1	for screw-in pins with shapes A, B and if necessary E
compatible with	Stucchi
Material	Stainless steel



Note

Interchangeable with couplings to ISO 16028.

Description

For a high flow with minimal pressure loss.
Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.
Suitable for use in environmentally sensitive areas.

Ordering information

Other pressure and temperature figures available on request.

Item

Identification	DN*	Connecting thread	Size	Operating pressure (bar)	SF coup.*	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKM 06 IR 1 FS VA	6	G 1/4" -19	1	400,0	4	-25	200
SKM 10 IR 2 FS VA	10	G 3/8" -19	2	250,0	4	-25	200
SKM 13 IR 2 FS VA	12	G 1/2" -14	2	250,0	4	-25	200
SKM 13 IR 3 FS VA	12	G 1/2" -14	3	250,0	4	-25	200
SKM 20 IR 3 FS VA	19	G 3/4" -14	3	250,0	4	-25	200
SKM 20 IR 4 FS VA	19	G 3/4" -14	4	250,0	4	-25	200
SKM 25 IR 5 FS VA	25	G 1" -11	5	250,0	4	-25	200

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

Product versions

SKM IR FS	Plug-in coupling sleeve, electro galvanised

Accessories

SKM ZUBS FS	Dust protection coupling sleeve, SKM..FS

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.