

# WA LF PN16

Connector ... LF, PN 16, steel

**HANSA FLEX**

## Properties

|                       |   |
|-----------------------|---|
| <b>Application</b>    | Connection fitting for metal hoses  |
| <b>Connection 1</b>   | Short stub end with loose flange at pressure rating PN16  |
| <b>Sealing form 1</b> | flat sealing  |
| <b>Standard</b>       | DIN 2674<br>DIN EN 1092-1   |
| <b>Application</b>    | soldered variant temperature resistant up to 200 °C<br>welded variant in stainless steel temperature resistant up to 550 °C |
| <b>Construction</b>   | straight  |
| <b>Material</b>       | Steel collar<br>Steel loose flange  |



## Ordering information

Other designs available on request

| Item           | DN  | PN (bar) | D (mm) | d1 (mm) | K (mm) | L (mm) |
|----------------|-----|----------|--------|---------|--------|--------|
| WA 010 LF PN16 | 10  | 16       | 90     | 40      | 60     | 14     |
| WA 013 LF PN16 | 13  | 16       | 95     | 45      | 65     | 14     |
| WA 020 LF PN16 | 20  | 16       | 105    | 58      | 75     | 14     |
| WA 025 LF PN16 | 25  | 16       | 115    | 68      | 85     | 14     |
| WA 032 LF PN16 | 32  | 16       | 140    | 78      | 100    | 18     |
| WA 040 LF PN16 | 40  | 16       | 150    | 88      | 110    | 18     |
| WA 050 LF PN16 | 50  | 16       | 165    | 102     | 125    | 18     |
| WA 065 LF PN16 | 65  | 16       | 185    | 122     | 145    | 18     |
| WA 080 LF PN16 | 80  | 16       | 200    | 138     | 160    | 18     |
| WA 100 LF PN16 | 100 | 16       | 220    | 158     | 180    | 18     |
| WA 125 LF PN16 | 125 | 16       | 250    | 188     | 210    | 18     |
| WA 150 LF PN16 | 150 | 16       | 285    | 212     | 240    | 22     |

## Product versions

WA LF PN16 VA Connector ... LF, PN 16, VA, Stainless steel collar