

# SKM IR FS MULTI FL

Multi-coupling fixed half flat

## Properties

<b>Application</b>	construction plant
<b>Connection 1</b>	BSP cylindrical internal threads
<b>Connection 2</b>	Plug in sleeve
<b>Residual pressure:</b>	Coupling under pressure to approx. 200 bar
<b>Design</b>	Multicoupling
<b>Construction type</b>	quick change system, 2 fold
<b>Scope of supply</b>	with weatherproof dust plate
<b>max: Flow</b>	90 L/min
<b>Material</b>	Steel
<b>Surface</b>	Zinc-nickel



## Description

extremely flat - optimal mechanics  
Stable design, high-strength and hardened materials  
Couple with one throw of a lever  
Modular construction

## Additional information

Multi couplings offer considerable benefits over bundled screw and plug-in couplings:

- Time saving factor due to fast and convenient exchange of add-on parts
- Convenient handling with simultaneous coupling of multiple connections
- Trouble-free coupling even if system pressures are applied
- No confusion between connections, no reversal of flow paths
- Flat seal valves prevent oil leakages, air admittance and allows efficient cleaning even in soiled working environments

## Item

Identification	Connecting thread	Operating pressure (bar)	Size
SKM 20 IR 3 FS MULTI FL	G 3/4" -14	330,0	3