

# SKS IR FS HA

Plug-in coupling plug

**HANSA FLEX**

## Properties

|                           |   |
|---------------------------|---|
| <b>Application</b>        | in construction, mining and tunnel building           |
| <b>Design</b>             | flat sealing  |
| <b>Connection 1</b>       | BSP cylindrical internal threads                      |
| <b>Sealing form 1</b>     | for screw-in pins with shapes A, B and if necessary E |
| <b>Standard</b>           | ISO 16028   |
| <b>Additional feature</b> | for breaker operation                                 |
| <b>compatible with</b>    | Stucchi   |
| <b>Material</b>           | Steel   |
| <b>Surface</b>            | electro galvanised                                    |



## Item

| Identification           | DN* | Connecting thread | Size | Operating pressure<br>(bar) | SF coup.* | Mineral oil temp. min.<br>(°C) | Mineral oil temp. max.<br>(°C) |
|--------------------------|-----|-------------------|------|-----------------------------|-----------|--------------------------------|--------------------------------|
| <b>SKS 20 IR 5 FS HA</b> | 19  | G 3/4" -14        | 5    | 350,0                       | 4         | -25                            | 100                            |
| <b>SKS 25 IR 5 FS HA</b> | 25  | G 1" -11          | 5    | 350,0                       | 4         | -25                            | 100                            |

DN = Nominal diameter, nominal width