

SKF IR FS

Screwed coupling fixed half, flat sealing

HANSA FLEX

Properties

| | |
|------------------------|---|
| Design | flat sealing |
| Connection 1 | BSP cylindrical internal threads |
| Sealing form 1 | for screw-in pins with shapes A, B and if necessary E |
| compatible with | Stucchi VEP |
| Material | Steel |
| Surface | electro galvanised |



Item

| Identification | Size | DN* | Connecting thread | Operating pressure (bar) | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) |
|----------------|------|-----|-------------------|--------------------------|-----------------------------|-----------------------------|
| SKF 06 IR 1 FS | 1 | 6 | G 1/4" -19 | 400,0 | -25 | 100 |
| SKF 10 IR 2 FS | 2 | 10 | G 3/8" -19 | 350,0 | -25 | 100 |
| SKF 13 IR 2F S | 2 | 12 | G 1/2" -14 | 350,0 | -25 | 100 |
| SKF 13 IR 3 FS | 3 | 12 | G 1/2" -14 | 350,0 | -25 | 100 |
| SKF 20 IR 3 FS | 3 | 19 | G 3/4" -14 | 350,0 | -25 | 100 |
| SKF 20 IR 4 FS | 4 | 19 | G 3/4" -14 | 350,0 | -25 | 100 |
| SKF 25 IR 4 FS | 4 | 25 | G 1" -11 | 325,0 | -25 | 100 |
| SKF 25 IR 5 FS | 5 | 25 | G 1" -11 | 325,0 | -25 | 100 |
| SKF 32 IR 5 FS | 5 | 31 | G 1.1/4" -11 | 300,0 | -25 | 100 |

DN = Nominal diameter, nominal width

Accessories

| | |
|-----------------|---------------------------|
| SKF ZUBS FS ALU | Dust protector for SKF FS |
|-----------------|---------------------------|