

# SKL IR FS

Screwed coupling, loose half, flat sealing

**HANSA FLEX**

## Properties

<b>Design</b>	flat sealing
<b>Connection 1</b>	BSP cylindrical internal threads
<b>Sealing form 1</b>	for screw-in pins with shapes A, B and if necessary E
<b>compatible with</b>	Stucchi VEP
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Item

Identification	Size	DN*	Connecting thread	Operating pressure (bar)	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
SKL 06 IR 1 FS	1	6	G 1/4" -19	400,0	-25	100
SKL 10 IR 2 FS	2	10	G 3/8" -19	350,0	-25	100
SKL 13 IR 2 FS	2	12	G 1/2" -14	350,0	-25	100
SKL 13 IR 3 FS	3	12	G 1/2" -14	350,0	-25	100
SKL 20 IR 3 FS	3	19	G 3/4" -14	350,0	-25	100
SKL 20 IR 4 FS	4	19	G 3/4" -14	350,0	-25	100
SKL 25 IR 4 FS	4	25	G 1" -11	325,0	-25	100
SKL 25 IR 5 FS	5	25	G 1" -11	325,0	-25	100
SKL 32 IR 5 FS	5	31	G 1.1/4" -11	300,0	-25	100

DN = Nominal diameter, nominal width

## Accessories

SKL ZUBS FS ALU Dust protector for SKL FS