

# SKM IN FS 700

Plug-in coupling boot, flat sealing, 700 bar

## Properties

|                        |   |
|------------------------|---|
| <b>Application</b>     | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| <b>Design</b>          | flat sealing  |
| <b>Connection 1</b>    | NPT internal thread   |
| <b>Sealing form 1</b>  | thread seal   |
| <b>compatible with</b> | Stucchi HP  |
| <b>Material</b>        | Steel   |
| <b>Surface</b>         | electro galvanised  |



## Item

| Identification             | DN* | Connecting thread | Size | Operating pressure (bar) | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) |
|----------------------------|-----|-------------------|------|--------------------------|-----------------------------|-----------------------------|
| <b>SKM 06 IN FS 700</b>    | 6   | NPT 1/4" -18      | 1    | 700,0                    | -25                         | 100                         |
| <b>SKM 06 IN 10 FS 700</b> | 6   | NPT 3/8" -18      | 1    | 700,0                    | -25                         | 100                         |

DN = Nominal diameter, nominal width

## Accessories

|                    |  |
|--------------------|--|
| <b>SKM ZUBS FS</b> | Dust protection coupling sleeve, SKM..FS |
|--------------------|--|