


# HK NTM

Level/temperature switch HK NTM

**HANSA FLEX**

## Properties

<b>Operating pressure</b>	max. 1 bar
<b>Operating temperature max.</b>	80 °C
<b>Connection</b>	G 3/4" male
<b>Operating voltage</b>	max. 230V AC
<b>Electrical connection</b>	Device connector M3 (3-polig)
<b>Protection IP</b>	IP 65
<b>Material</b>	Float SK 601 - hard PU Switching tube - brass Gasket: NBR
<b>Hysteresis</b>	± 5 K



## Description

One permanently set switching point (NC contact) for level and temperature

## Item

Identification	L (mm)	Switching point (°C)	Switching point (mm)	Weight (kg)
HK NTM M3 140 60NC 280	280	60	140	0,30
HK NTM M3 140 70NC 280	280	70	140	0,30
HK NTM M3 140 80NC 280	280	80	140	0,30
HK NTM M3 190 60NC 280	280	60	190	0,30
HK NTM M3 190 70NC 280	280	70	190	0,30
HK NTM M3 190 80NC 280	280	80	190	0,30
HK NTM M3 320 60NC 370	370	60	320	0,40
HK NTM M3 320 70NC 370	370	70	320	0,40
HK NTM M3 320 80NC 370	370	80	320	0,40

Switching point (°C) = temperature switching point – Switching point (mm) = level switching point