

HK B3/B14 230/400V

Electric motor B3/B14 230/400V

HANSA FLEX

Properties

Design	type B3/B14 feet removable
Protection IP	IP 55
Ambient temperature	-20 °C to +40 °C
Material	Housing: Aluminium painted



Description

Self-cooling squirrel-cage motors

Rated voltage 230/400V 50Hz, 460V 60Hz; 4-pin

Item

Identification	n 50 Hz (rpm)	P 50 Hz (kW)	I 50 Hz (A)	LF 50 Hz	H (mm)	A (mm)	B (mm)	C (mm)	Ø D shaft (mm)	Ø E (mm)	Ø F (mm)	Weight (kg)
HK K 401 FCPA	1360	0,18	0,60	0,73	63	100	194	174	11	60	90	4,5
HK K 402 FCPA	1380	0,25	0,80	0,74	71	112	215	189	14	70	105	6,0
HK K 403 FCPA	1380	0,37	1,10	0,75	71	112	215	189	14	70	105	6,5
HK K 404 FCPA	1380	0,55	1,50	0,75	80	125	250	209	19	80	120	9,0

P 50 Hz = nominal output at 400 V/50 Hz – n 50 Hz = nominal speed at 400 V/50 Hz – I 50 Hz = nominal current at 400 V/50 Hz – LF 50 Hz = cos phi power factor at 50 Hz