

Properties

| | |
|-----------------|--|
| Design | for pressure, differential pressure, temperature, volumetric flow and speed 50/sec measurement rate |
| Scope of supply | incl. PC connection cable and software incl. power supply 230 V / 50 Hz |



Note

For storing the measurement sequence during measuring the appliance must be connected to a PC on which the enclosed software has been installed

Description

5-channel gauge for simultaneous measurement of pressure, differential pressure, volumetric flow and
temperature.

Simultaneous connection of max. 4 sensors (2x pressure, 1x temperature, 1x volumetric flow).

A speed sensor can be connected in place of the volumetric flow sensor.

Graphic display with background lighting.

Oil-resistant film keypad.

Convenient menu navigation, different languages and unit systems can be selected.

Data interface RS 232 / USB adapter.

Sensor detection, self-diagnostics and battery check integrated.

Automatic zero-point correction.

Min/max storage (no storage of complete measurement sequence).

Average value memory of 10sec or 20sec.

Ordering information

This gauge can be combined with the included accessories to a measuring case.

1 gauge, 1 measuring turbine and various sensors incl. cable and operating manual can be packed into the HK KS33 case.

Further accessories and gauges with additional options available on request.

Item

| Identification | Weight (kg) |
|----------------|----------------|
| HK PTQ CHECK5 | 0,5 |

Accessories

| | |
|-----------|--|
| HK 622 | Measuring turbine |
| HK PTA | Pressure sensor |
| HK TS TP | Temperature sensor |
| HK DS 100 | Speed sensor |
| HK PML | Single instrumentation cable |
| HK PQT | Combination instrumentation cable |
| HK KS33 | Protective case for measuring instrument |