
## DAMPF HR MG

Steam fittings HR, with brass clamping shell



Properties				
Application	Hot water or saturated steam applications			
Connection 1	BSPT conical external threads			
Sealing form 1	flat sealing			
Operating pressure	up to 18 bar			
Short code	AGR-Flat			
Standard	DIN EN 14423 thread standard ISO 228/DIN 2999			
Scope of supply	with clamping shells			
Temp. range	saturated steam up to +210 °C hot water up to +120 °C			
Material	Brass Pressed brass clamping shells			





Item							
Identification	DN	Size	Inches	G1	L (mm)	Clamping range (mm)	S1 (mm)
DAMPF 13 HR MG	12	8	1/2"	G 1/2" -14	95,0	24 - 26	22
DAMPF 19 HR MG	19	12	3/4"	G 3/4" -14	95,0	32 - 34	27
DAMPF 25 HR MG	25	16	1"	G 1" -11	100,0	39 - 41	36
DAMPF 32 HR MG	31	20	1.1/4"	G 1.1/4" -11	105,0	47 - 50	46
DAMPF 38 HR MG	38	24	1.1/2"	G 1.1/2" -11	125,0	53 - 56	50
DAMPF 50 HR MG	51	32	2"	G 2" -11	140,0	67 - 69	60

DN = Nominal diameter, nominal width

Product versions		
DAMPF AR	Steam fittings AR, with steel clamping shell, Steel	
DAMPF AR VA	Steam fittings AR, with stainless steel clamping shell, Stainless steel	