
DAMPF AR VA

Steam fittings AR, with stainless steel clamping shell

Properties

Application	Hot water or saturated steam applications
Connection 1	BSP nut thread
Sealing form 1	flat sealing
Operating pressure	up to 18 bar
Short code	DKR flat
Standard	DIN EN 14423 thread standard ISO 228/DIN 2999
Scope of supply	with clamping shells and seal
Temp. range	saturated steam up to +210 °C hot water up to +120 °C
Material	Stainless steel Stainless steel clamping shells





Item

Identification	DN	Size	Inches	G1	L (mm)	Clamping range (mm)	S1 (mm)
DAMPF 13 AR VA	12	8	1/2"	G 1/2" -14	88,0	24 - 26	27
DAMPF 19 AR VA	19	12	3/4"	G 3/4" -14	92,0	32 - 34	32
DAMPF 25 AR VA	25	16	1"	G 1" -11	93,0	39 - 41	41
DAMPF 32 AR VA	31	20	1.1/4"	G 1.1/4" -11	97,5	47 - 50	-
DAMPF 38 AR VA	38	24	1.1/2"	G 1.1/2" -11	120,0	53 - 56	55
DAMPF 50 AR VA	51	32	2"	G 2" -11	131,0	67 - 69	70

DN = Nominal diameter, nominal width

Product versions

DAMPF AR	Steam fittings AR, with steel clamping shell, Steel
DAMPF AR MG	Steam fittings AR, with clamping brass shell, Brass

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.