PA 700 SF6 PLUS

Swage fitting, SFS

HANSA-FLEX

Properties

Application	Swage fitting for HD 700 PLUS hoses
Connection 1	SAE flange connection 6000 PSI
Sealing form 1	flat seal with SF O-ring
Short code	SFS
Standard	SAE J518 ISO 6162-2
Integration	with pull-out protection (interlock)
Scope of supply	Swage nipple + swage ferrule
Material	Steel
Surface	electro galvanised





Item

Identification	DN	Size	Inches	Flange size	Operating pressure (bar)	D (mm)	H (mm)	L1 (mm)	L2 (mm)
PA 720 SF6 PLUS	19	12	3/4"	3/4"	420,0	41,3	8,8	110,6	-
PA 720 SF6 25 PLUS	19	12	3/4"	1"	420,0	47,6	9,6	118,2	-
PA 725 SF6 PLUS	25	16	1"	1"	420,0	47,6	9,6	134,0	-
PA 725 SF6 32 PLUS	25	16	1"	1.1/4"	420,0	54,0	10,5	134,9	-
PA 732 SF6 25 PLUS	31	20	1.1/4"	1"	420,0	47,6	9,6	166,4	-
PA 732 SF6 PLUS	31	20	1.1/4"	1.1/4"	420,0	54,0	10,5	145,2	-
PA 732 SF6 L 115 PLUS	31	20	1.1/4"	1.1/4"	420,0	54,0	10,5	189,9	115,0
PA 732 SF6 40 PLUS	31	20	1.1/4"	1.1/2"	420,0	63,5	12,6	162,0	-
PA 740 SF6 PLUS	38	24	1.1/2"	1.1/2"	420,0	63,5	12,6	203,0	-
PA 750 SF6 PLUS	51	32	2"	2"	420,0	79,4	12,6	200,8	-

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.