

Properties	
Design	Configuration and delivery on request. with manual or electric magnet-valves
Operating pressure	max. 700 bar
Volumetric flow	0,36 - 4,00 l/min



## Note

Attention: Please observe separate safety precautions for working with 700 bar equipment (see technical information)!

## Description

electro-hydraulic pumps (compact power packs) to supply medium and heavy-duty cylinders

Tank size: 2.5 - 100 litre (tanks steel or aluminium)

Electric motors for 115 V, 230 V, 400 V

Optional accessories: Protective brackets, transport rollers, oil coolers

## **Ordering information**

No stock goods, configuration (in fixed graduations) and delivery period upon request!

## Item

Item	
Identification	Design
Elektrohydraulische Pumpe HBM	Manually switched directional control valve
Elektrohydraulische Pumpe HBE	Electrically switched directional control valve

Accessories	
NY 2100	Thermoplastic extreme pressure hose
GKS	Rubber antikink protection
PNY 2100 HN	Swage nipple, AGN
PHY 2100	Swage ferrule, NY 2100
SKL HN SP	Screwed coupling, loose half
SKL ZUBS SP	Dust protection for SKLSP
SKF IN SP	Screwed coupling fixed half
SKF ZUBS SP	Dust protection for SKFSP