

### Properties

<b>Design</b>	Configuration and delivery on request. with manual or electric magnet-valves
<b>Operating pressure</b>	max. 700 bar
<b>Volumetric flow</b>	0,36 - 4,00 l/min



### Note

Attention: Please observe separate safety precautions for working with 700 bar equipment (see technical information)!

### Description

electro-hydraulic pumps (compact power packs) to supply medium and heavy-duty cylinders

Tank size: 2.5 - 100 litre (tanks steel or aluminium)

Electric motors for 115 V, 230 V, 400 V

Optional accessories: Protective brackets, transport rollers, oil coolers

### Ordering information

No stock goods, configuration (in fixed graduations) and delivery period upon request!

### Item

Identification	Design
<b>Elektrohydraulische Pumpe HBM</b>	Manually switched directional control valve
<b>Elektrohydraulische Pumpe HBE</b>	Electrically switched directional control valve

### Accessories

<b>NY 2100</b>	Thermoplastic extreme pressure hose
<b>GKS</b>	Rubber antikink protection
<b>PNY 2100 HN</b>	Swage nipple, AGN
<b>PHY 2100</b>	Swage ferrule, NY 2100
<b>SKL HN SP</b>	Screwed coupling, loose half
<b>SKL ZUBS SP</b>	Dust protection for SKL...SP
<b>SKF IN SP</b>	Screwed coupling fixed half
<b>SKF ZUBS SP</b>	Dust protection for SKF...SP