

### Properties

|                           |   |
|---------------------------|---|
| <b>Design</b>             | Configuration and delivery on request.<br>with manual or electric magnet-valves |
| <b>Operating pressure</b> | max. 700 bar  |
| <b>Volumetric flow</b>    | 0,36 - 4,00 l/min   |



### Note

Attention: Please observe separate safety precautions for working with 700 bar equipment (see technical information)!

### Description

electro-hydraulic pumps (compact power packs) to supply medium and heavy-duty cylinders  
Tank size: 2.5 - 100 litre (tanks steel or aluminium)  
Electric motors for 115 V, 230 V, 400 V  
Optional accessories: Protective brackets, transport rollers, oil coolers

### Ordering information

No stock goods, configuration (in fixed graduations) and delivery period upon request!

### Item

| Identification                       | Design  |
|--------------------------------------|---|
| <b>Elektrohydraulische Pumpe HBM</b> | Manually switched directional control valve     |
| <b>Elektrohydraulische Pumpe HBE</b> | Electrically switched directional control valve |

### Accessories

|                    |                                     |
|--------------------|-------------------------------------|
| <b>NY 2100</b>     | Thermoplastic extreme pressure hose |
| <b>GKS</b>         | Rubber antikink protection          |
| <b>PNY 2100 HN</b> | Swage nipple, AGN                   |
| <b>PHY 2100</b>    | Swage ferrule, NY 2100              |
| <b>SKL HN SP</b>   | Screwed coupling, loose half        |
| <b>SKL ZUBS SP</b> | Dust protection for SKL...SP        |
| <b>SKF IN SP</b>   | Screwed coupling fixed half         |
| <b>SKF ZUBS SP</b> | Dust protection for SKF...SP        |