


Properties	
Operating pressure	max. 700 bar
Surface	phosphate treated
Material	Steel C45





## Ordering information

Other screw fittings on request.

Item							
Identification	Design	A	В	С	D (mm)	E (mm)	Weight (kg)
HK HV NAA 14 14	Male thread/Male thread connector	NPT 1/4"	NPT 1/4" -18	-	38	-	0,05
HK HV NAA 38 38	Male thread/Male thread connector	NPT 3/8" -18	NPT 3/8" -18	-	51	-	0,05
HK HV ZII 14 14	Female thread/female thread connector	NPT 1/4"	NPT 1/4" -18	-	29	-	0,08
HK HV ZII 38 38	Female thread/female thread connector	NPT 3/8" -18	NPT 3/8" -18	-	36	-	0,08
HK HV RAI 38 14	Male thread/female thread reduction	NPT 1/4"	NPT 3/8" -18	-	35	-	0,15
HK HV RII 38 14	Female thread/female thread reduction	NPT 1/4"	NPT 3/8" -18	-	28	-	0,14
HK HV WAI 38 38	Male thread/female thread elbow	NPT 3/8" -18	NPT 3/8" -18	-	45	35	0,16
HK HV WII 38 38	Female thread/female thread elbow	NPT 3/8" -18	NPT 3/8" -18	-	35	35	0,16
HK HV TIII 14 14 14	Female thread/female thread/female thread T-piece	NPT 1/4"	NPT 1/4" -18	NPT 1/4" -18	45	35	0,20
HK HV TIII 38 38 38	Female thread/female thread T-piece	NPT 3/8" -18	NPT 3/8" -18	NPT 3/8" -18	45	35	0,20

Accessories			
NY 2100	Thermoplastic extreme pressure hose		
GKS	Rubber antikink protection		
PNY 2100 HN	Swage nipple, AGN		
PHY 2100	Swage ferrule, NY 2100		
SKL HN SP	Screwed coupling, loose half		
SKL ZUBS SP	Dust protection for SKLSP		
SKF IN SP	Screwed coupling fixed half		
SKF ZUBS SP	Dust protection for SKFSP		