

# PA 700 SF 90 PLUS

Swage fitting, SFL angle 90°

**HANSA FLEX**

## Properties

<b>Application</b>	Swage fitting for HD 700 PLUS hoses
<b>Connection 1</b>	SAE flange connection 3000 PSI
<b>Sealing form 1</b>	flat seal with SF O-ring
<b>Short code</b>	SFL
<b>Standard</b>	SAE J518 ISO 6162-1
<b>Integration</b>	with pull-out protection (interlock)
<b>Scope of supply</b>	Swage nipple + swage ferrule
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Item

Identification	DN	Size	Inches	Flange size	D (mm)	H (mm)	L1 (mm)	L2 (mm)
PA 720 SF 25 90 PLUS	19	12	3/4"	1"	44,5	8,1	139,8	71,0
PA 725 SF 90 PLUS	25	16	1"	1"	44,5	8,1	155,6	71,0
PA 725 SF 32 90 L 80 PLUS	25	16	1"	1.1/4"	50,8	8,1	144,0	80,0
PA 725 SF 32 90 L 100 PL	25	16	1"	1.1/4"	50,8	8,1	174,3	100,0
PA 750 SF 90 PLUS	50	32	2"	2"	71,4	8,1	247,6	134,0