

PA 700 SK6 15 PLUS

Swage fitting, SK6 angle 15°

HANSA FLEX

Properties

| | |
|---------------------------|--------------------------------------|
| Application | Swage fitting for HD 700 PLUS hoses |
| Connection 1 | SAE flange connection 6000 PSI |
| Sealing form 1 | flat seal with SF O-ring |
| Integration | with pull-out protection (interlock) |
| Scope of supply | Swage nipple + swage ferrule |
| Additional feature | cone SAE fitting |
| Material | Steel |
| Surface | electro galvanised |



Item

| Identification | DN | Size | Inches | Flange size | D (mm) | M metr. | L1 (mm) | L2 (mm) | A (mm) | B (mm) | C (mm) | E (mm) |
|--------------------------|----|------|--------|-------------|-----------|-----------|------------|------------|-----------|-----------|-----------|-----------|
| PA 725 SK6 15 PLUS | 25 | 16 | 1" | 1" | 57,4 | M 12 x 50 | 199,1 | 14,0 | 57,2 | 27,8 | 27,0 | 13 |
| PA 732 SK6 15 L 20 PLUS | 31 | 20 | 1.1/4" | 1.1/4" | 57,4 | | 229,0 | 20,0 | 66,6 | 31,8 | 32,0 | 15 |
| PA 732 SK6 40 15 L 20 PL | 31 | 20 | 1.1/4" | 1.1/2" | 68,4 | | 254,0 | 20,3 | 79,3 | 36,5 | 40,0 | 17 |
| PA 740 SK6 15 PLUS | 38 | 24 | 1.1/2" | 1.1/2" | 68,4 | | 293,0 | 25,0 | 79,3 | 36,5 | 40,0 | 17 |
| PA 750 SK6 15 PLUS | 51 | 32 | 2" | 2" | 83,5 | | 303,0 | 25,0 | 96,8 | 44,5 | 50,0 | 21 |

Accessories

| | |
|----------------------|------------------------------|
| FS | Seal for SAE and ISO flanges |
| SCHRAUBE M | Hexagon socket screw |
| SCHRAUBE M VZ | Hexagon socket screw |