


PA 700 SK6 22,5 PLUS

Swage fitting, SK6 angle 22,5°

HANSA FLEX

Properties

| | |
|---------------------------|--------------------------------------|
| Application | Swage fitting for HD 700 PLUS hoses |
| Connection 1 | SAE flange connection 6000 PSI |
| Sealing form 1 | flat seal with SF O-ring |
| Integration | with pull-out protection (interlock) |
| Scope of supply | Swage nipple + swage ferrule |
| Additional feature | cone SAE fitting |
| Material | Steel |
| Surface | electro galvanised |



Item

| Identification | DN | Size | Inches | Flange size | D (mm) | M metr. | L1 (mm) | L2 (mm) | A (mm) | B (mm) | C (mm) | E (mm) |
|----------------------|----|------|--------|-------------|-----------|---------|------------|------------|-----------|-----------|-----------|-----------|
| PA 740 SK6 22.5 PLUS | 38 | 24 | 1.1/2" | 1.1/2" | 68,4 | | 296,0 | 38,0 | 79,3 | 36,5 | 40,0 | 17 |
| PA 750 SK6 22.5P LUS | 51 | 32 | 2" | 2" | 83,5 | | 315,0 | 45,0 | 96,8 | 44,5 | 50,0 | 21 |

Accessories

| | |
|----------------------|------------------------------|
| FS | Seal for SAE and ISO flanges |
| SCHRAUBE M | Hexagon socket screw |
| SCHRAUBE M VZ | Hexagon socket screw |