## PA 700 SK6 100 PLUS


Swage fitting, SK6 angle 100°



## Properties

1 Toportioo					
Application	Swage fitting for HD 700 PLUS hoses				
Connection 1	SAE flange connection 6000 PSI				
Sealing form 1	flat seal with SF O-ring				
Integration	with pull-out protection (interlock)				
Scope of supply	Swage nipple + swage ferrule				
Additional feature	nal feature cone SAE fitting				
Material	Steel				
Surface	electro galvanised				





## Item

(mm) (m) (m) (m) (m) (m) (m) (m) (m) <th>Identification</th> <th>DN</th> <th>Size</th> <th>Inches</th> <th>Flange size</th> <th>D</th> <th>M metr.</th> <th>L1</th> <th>L2</th> <th>А</th> <th>В</th> <th>С</th> <th>E</th>	Identification	DN	Size	Inches	Flange size	D	M metr.	L1	L2	А	В	С	E
<b>PA 750 SK6 100 PLUS</b> 51 32 2" 2" 83,5 196,0 195,0 96,8 44,5 50,0 21						(mm)		(mm)	(mm)	(mm)	(mm)	(mm)	(mm)
	PA 750 SK6 100 PLUS	51	32	2"	2"	83,5		196,0	195,0	96,8	44,5	50,0	21

## Accessories

FS	Seal for SAE and ISO flanges						
SCHRAUBE M	Hexagon socket screw						
SCHRAUBE M VZ	Hexagon socket screw						