
HK DKE X 00 DC

Solenoid-operated directional control valve size10 without coil



Properties		
Design	4/2-way valve or 4/3-way valve 5-chamber valve with manual emergency operation for DC coils	
Scope of supply	without coil or plug	
Operating pressure	P, A, B: max. 315bar / T: max. 210bar	
Volumetric flow	max. 120 l/min (note characteristic curves)	
Connection	ISO/Cetop 05 size 10	
Mounting	4 pcs. socket head screw M6x40 12.9	





Description

Can only be used for DC coils switching capacity limits see characteristic curves

Ordering information

Further circuits and versions, volumetric flows and switching power limits on request

Item					
Identification	Туре	Overlap	Piston type	Design	Weight (kg)
HK DKE 1 610 X00DC	4/2	negative (open)	0 [PB/AT]-[ABPT]	Spring return	3,8
HK DKE 1 611 X00DC	4/2	positive (closed)	1 [PB/AT]-[A/B/P/T]	Spring return	3,8
HK DKE 1 613 X00DC	4/2	positive (closed)	3 [PB/AT]-[ABT/P]	Spring return	3,8
HK DKE 1 631 2 X00DC	4/2	positive (closed)	1/2 [PB/AT]-[PA/BT]	Spring return	3,8
HK DKE 1 631 2 A X00DC	4/2	positive (closed)	1/2 [PB/AT]-[PA/BT]	Spring return	3,8
HK DKE 1 632 2 X00DC	4/2	positive (closed)	2/2 [PB/A/T]-[PA/B/T]	Spring return	3,8
HK DKE 1 710 X00DC	4/3	negative (open)	0 [PB/AT]-[ABPT]-[PA/BT]	spring return to 0	4,1
HK DKE 1 711 X00DC	4/3	positive (closed)	1 [PB/AT]-[A/B/P/T]-[PA/BT]	spring return to 0	4,1
HK DKE 1 713 X00DC	4/3	positive (closed)	3 [PB/AT]-[ABT/P]-[PA/BT]	spring return to 0	4,1
HK DKE 1 714 X00DC	4/3	negative (open)	4 [PA/BT]-[A/B/PT]-[PB/AT]	spring return to 0	4,1
HK DKE 1 751 2 X00DC	4/2	positive (closed)	1/2 [PB/AT]-[PA/BT]	2 latching positions	3,8

Piston type example: [A/B/PT] = [A blocked / B blocked / P+T connected]

Accessories		
HK SP CAE	Coil for solenoid-operated directional control valve HK DKE	
HK SP DIN 43650	Electrical plug for solenoid coil DIN 43650 / ISO 4400	
HK M HK DK	Set of bolts for NG 10 valves types HK DK11/DKE/DG4V5	
HK SP WPD / SP SET / 6 OE Emergency hand operation for directional solenoid valve		