

# SKM IN FS

Plug-in coupling boot, flat sealing

**HANSA FLEX**

## Properties

<b>Application</b>	General application, e.g. in industry, construction machinery, agricultural technology etc.
<b>Design</b>	flat sealing
<b>Connection 1</b>	NPT internal thread
<b>compatible with</b>	Stucchi
<b>Material</b>	Steel
<b>Surface</b>	electro galvanised



## Note

Interchangeable with couplings to ISO 16028.

## Description

Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.

For a high flow with minimal pressure loss.

Suitable for use in environmentally sensitive areas.

## Ordering information

Other pressure and temperature figures available on request.

Item						
Identification	DN*	Connecting thread	Size	Operating pressure (bar)	Mineral oil temp. min. (°C)	Mineral oil temp. max. (°C)
<b>SKM 10 IN 2 FS</b>	10	NPT 3/8" -18	2	350,0	-25	100
<b>SKM 13 IN 2 FS</b>	12	NPT 1/2" -14	2	350,0	-25	100
<b>SKM 13 IN 3 FS</b>	12	NPT 1/2" -14	3	350,0	-25	100

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled