

SKM IN FS

Plug-in coupling boot, flat sealing

Properties

| | |
|------------------------|---|
| Application | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| Design | flat sealing |
| Connection 1 | NPT internal thread |
| compatible with | Stucchi |
| Material | Steel |
| Surface | electro galvanised |



Note

Interchangeable with couplings to ISO 16028.

Description

Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.
For a high flow with minimal pressure loss.
Suitable for use in environmentally sensitive areas.

Ordering information

Other pressure and temperature figures available on request.

Item

| Identification | DN* | Connecting thread | Size | Operating pressure (bar) | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) |
|-----------------------|-----|-------------------|------|--------------------------|-----------------------------|-----------------------------|
| SKM 10 IN 2 FS | 10 | NPT 3/8" -18 | 2 | 350,0 | -25 | 100 |
| SKM 13 IN 2 FS | 12 | NPT 1/2" -14 | 2 | 350,0 | -25 | 100 |
| SKM 13 IN 3 FS | 12 | NPT 1/2" -14 | 3 | 350,0 | -25 | 100 |

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled