# SKS IN FS

Plug-in coupling plug, flat sealing

## Properties

| | |
|---|---|
| **Application** | General application, e.g. in industry, construction machinery, agricultural technology etc. |
| **Design** | flat sealing |
| **Connection 1** | NPT internal thread |
| **Material** | Steel |
| **Surface** | electro galvanised |



## Note

Interchangeable with couplings to ISO 16028.

## Description

Flat seal plug-in coupling for minimal oil leakages and air admittance when coupling.
For a high flow with minimal pressure loss.
Suitable for use in environmentally sensitive areas.

## Item

| Identification | DN* | Connecting thread | Size | Operating pressure (bar) | Mineral oil temp. min. (°C) | Mineral oil temp. max. (°C) |
|---|---|---|---|---|---|---|
| **SKS 10 IN 2 FS** | 10 | NPT 3/8" -18 | 2 | 350,0 | -25 | 100 |
| **SKS 13 IN 2 FS** | 12 | NPT 1/2" -14 | 2 | 350,0 | -25 | 100 |
| **SKS 13 IN 3 FS** | 12 | NPT 1/2" -14 | 3 | 350,0 | -25 | 100 |

DN = Nominal diameter, nominal width – SF gek. = Safety factor coupled

*Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.*