


PA 800 AOS 45

Swage fitting, DKOS angle 45°

Properties

Application	Swage fitting for HD 800 hoses
Connection 1	metric nut thread
Sealing form 1	24° outer cone with O-ring
Standard	ISO 8434-1
Short code	DKOS
Integration	with pull-out protection (interlock)
Scope of supply	Swage nipple + swage ferrule
Material	Steel
Surface	electro galvanised



Note

Added innovative and unique new O-ring seal 27,3mm x 2,4mm (Material:EPDM)to the -20 size nipples. The O-ring design prevents fluid migration thus providing zero leakage as measured to SAE and EN specifications

Item

Identification	DN*	Size	Inches	G1	for external pipe Ø (mm)	L1 (mm)	L2 (mm)	S1	Operating pressure (bar)	OR
PA 816 AOS 45	16	10	3/8"	M 30 x 2	20	112,8	31,0	36	500,0	17.5 x 2.5
PA 816 AOS 20 45	16	10	3/8"	M 36 x 2	25	-	32,0	46	500,0	20.0 x 2.5
PA 820 AOS 16 45	19	12	3/4"	M 30 x 2	20	124,4	28,2	36	420,0	17.5 x 2.5
PA 820 AOS 45	19	12	3/4"	M 36 x 2	25	135,1	32,0	46	500,0	20.0 x 2.5
PA 825 AOS 20 45	25	16	1"	M 36 x 2	25	145,7	32,9	41	420,0	20.0 x 2.5
PA 825 AOS 45	25	16	1"	M 42 x 2	30	163,6	35,0	50	500,0	25.0 x 2.5
PA 832 AOS 45	31	20	1.1/4"	M 52 x 2	38	190,0	39,0	60	500,0	33.0 x 2.5