
PA 800 AOS
Swage fitting, DKOS

Properties

Application	Swage fitting for HD 800 hoses
Connection 1	metric nut thread
Sealing form 1	24° outer cone with O-ring
Standard	ISO 8434-1
Short code	DKOS
Integration	with pull-out protection (interlock)
Scope of supply	Swage nipple + swage ferrule
Material	Steel
Surface	electro galvanised





Note

Added innovative and unique new O-ring seal 27,3mm x 2,4mm (Material:EPDM)to the -20 size nipples. The O-ring design prevents fluid migration thus providing zero leakage as measured to SAE and EN specifications

Item

Identification	DN*	Size	Inches	G1	for external pipe Ø (mm)	L1 (mm)	S1	Operating pressure (bar)	OR
PA 816 AOS	16	10	5/8"	M 30 x 2	20	80,5	36	500,0	17.5 x 2.5
PA 816 AOS 20	16	10	5/8"	M 36 x 2	25	-	-	500,0	20.0 x 2.5
PA 820 AOS 16	19	12	3/4"	M 30 x 2	20	103,2	36	420,0	17.5 x 2.5
PA 820 AOS	19	12	3/4"	M 36 x 2	25	103,2	46	500,0	20.0 x 2.5
PA 825 AOS 20	25	16	1"	M 36 x 2	25	122,0	41	420,0	20.0 x 2.5
PA 825 AOS	25	16	1"	M 42 x 2	30	120,6	50	500,0	25.0 x 2.5
PA 832 AOS	31	20	1.1/4"	M 52 x 2	38	134,9	60	500,0	33.0 x 2.5

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.