

# SFCE (6000 PSI)

## SAE external thread flange

### Properties

<b>Pressure series</b>	6000 psi
<b>Standard</b>	DIN 3901/3902
<b>Construction</b>	straight
<b>Design</b>	SAE external thread flange
<b>Scope of supply</b>	connecting piece only
<b>Material</b>	S355J2G3 (C22)
<b>Surface</b>	electro galvanised



### Note

In accordance with SAE J 518 C, the specified nominal pressure is defined by the flange or based on the pipe to be welded on. Recommended screws are listed in the columns M (metr) and M (unc).

### Item

Identification	Series	Ø RAD (mm)	PB 10.9 (bar)	Size	A	A1 (mm)	Ø B (mm)	G1 (mm)	G2 (mm)	I (mm)	L (mm)	M metr.	M unc
SFCE 6001 S16	S	16	400	1/2"	M24x1,5	31,7	12	53,2	63	8,5	8,5	M 8 x 30	5/16" x 1.1/4"
SFCE 6002 S16	S	16	400	3/4"	M24x1,5	41,3	12	59,2	69	8,5	10,5	M 10 x 35	3/8" x 1.1/2"
SFCE 6002 S20	S	20	400	3/4"	M30x2	41,3	16	61,2	72	10,5	10,5	M 10 x 35	3/8" x 1.1/2"
SFCE 6002 S25	S	25	400	3/4"	M36x2	41,3	17	63,2	75	12,0	10,5	M 10 x 35	3/8" x 1.1/2"
SFCE 6002 S30	S	30	400	3/4"	M42x2	41,3	18	64,0	77	13,5	10,5	M 10 x 35	3/8" x 1.1/2"
SFCE 6003 S25	S	25	400	1"	M36x2	47,6	20	72,2	84	12,0	*1	M 12 x 45	7/16" x 1.3/4"
SFCE 6003 S30	S	30	400	1"	M42x2	47,6	24	74,0	87	13,5	*1	M 12 x 45	7/16" x 1.3/4"
SFCE 6004 S30	S	30	400	1.1/4"	M42x2	54,0	25 / 30	79,2	92	13,5	*2	M 14 x 50	1/2" x 1.3/4"
SFCE 6004 S38	S	38	350	1.1/4"	M52x2	54,0	30	83,2	98	16,0	*2	M 14 x 50	1/2" x 1.3/4"
SFCE 6005 S38	S	38	350	1.1/2"	M52x2	63,5	30	89,2	104	16,0	16,7	M 16 x 55	1/2" x 1.3/4"

PN = Nominal pressure PB = Max. operating pressure – Series: LL = Very light L = Light S = Heavy

\*1) = Choice of 12.0 or 12.5 – \*2) = Choice of 13.5 or 14.5

### Product versions

<b>SFCE M (3000 / 6000 PSI)</b>	SAE external thread flange, with 2 flange halves, screw set, O-ring, nut and cutting ring
<b>SFCE U (3000 / 6000 PSI)</b>	SAE external thread flange, with 2 flange halves, screw set, O-ring, nut and cutting ring