
HK DKE X 00 AC

Solenoid-operated directional control valve size10 without coil



Properties		
Design	4/2-way valve or 4/3-way valve 3-chamber valve with manual emergency operation for AC coils	
Scope of supply	without coil or plug	
Operating pressure	P, A, B: max. 350bar / T: max. 160bar	
Volumetric flow	max. 150 l/min (note characteristic curves)	
Connection	ISO/Cetop 05 size 10	
Mounting	4 pcs. socket head screw M6x40 12.9	





Description

Can only be used for AC coils switching capacity limits see characteristic curves

Ordering information

Further circuits and versions, volumetric flows and switching power limits on request

Item					
Identification	Туре	Overlap	Piston type	Design	Weight (kg)
HK DKE 1610 X 00AC	4/2	negative (open)	0 [PB/AT]-[ABPT]	Spring return	3,6
HK DKE 1611 X 00AC	4/2	positive (closed)	1 [PB/AT]-[A/B/P/T]	Spring return	3,6
HK DKE 1613 X 00AC	4/2	positive (closed)	3 [PB/AT]-[ABT/P]	Spring return	3,6
HK DKE 1631 2 A 00AC	4/2	positive (closed)	1/2 [PB/AT]-[PA/BT]	Spring return	3,6
HK DKE 1631 2 X 00AC	4/2	positive (closed)	1/2 [PB/AT]-[PA/BT]	Spring return	3,6
HK DKE 1632 2 X 00AC	4/2	positive (closed)	2/2 [PB/A/T]-[PA/B/T]	Spring return	3,6
HK DKE 1710 X 00AC	4/3	negative (open)	0 [PB/AT]-[ABPT]-[PA/BT]	spring return to 0	4,1
HK DKE 1711 X 00AC	4/3	positive (closed)	1 [PB/AT]-[A/B/P/T]-[PA/BT]	spring return to 0	4,1
HK DKE 1713 X 00AC	4/3	positive (closed)	3 [PB/AT]-[ABT/P]-[PA/BT]	spring return to 0	4,1
HK DKE 1714 X 00AC	4/3	negative (open)	4 [PA/BT]-[A/B/PT]-[PB/AT]	spring return to 0	4,1
HK DKE 1751 2 X 00AC	4/2	positive (closed)	1/2 [PB/AT]-[PA/BT]	2 latching positions	3,3

Piston type example: [A/B/PT] = [A blocked / B blocked / P+T connected]

Accessories	
HK SP CAE	Coil for solenoid-operated directional control valve HK DKE
HK SP DIN 43650	Electrical plug for solenoid coil DIN 43650 / ISO 4400
HK M HK DK	Set of bolts for NG 10 valves types HK DK11/DKE/DG4V5
HK SP WPD / SP SET / 6 OE	Emergency hand operation for directional solenoid valve