


## Properties

<b>Connection 1</b>	Fixed flange at pressure rating PN16
<b>Construction</b>	straight
<b>Sealing form 1</b>	flat sealing
<b>Application</b>	Industry
<b>Standard</b>	DIN EN 1092-1
<b>Material</b>	Stainless steel



## Item

Identification	DN*	Size	Inches	Ø D (mm)	K (mm)	Ø d2 (mm)	N (mm)
TUE G 25 FF PN16 VA	25	16	1"	115,0	85	14	4
TUE G 32 FF PN16 VA	32	20	1.1/4"	140,0	100	18	4
TUE G 38 FF PN16 VA	40	24	1.1/2"	150,0	110	18	4
TUE G 50 FF PN16 VA	50	32	2"	165,0	125	18	4
TUE G 63 FF PN16 VA	63	40	2.1/2"	-	-	-	-
TUE G 75 FF PN16 VA	75	50	3"	200,0	160	18	8
TUE G 102 FF PN16 VA	100	64	4"	220,0	180	18	8

N = number of holes

## Accessories

<b>KS AL</b>	Clamp ring fitting, aluminium
<b>KS FIX AL</b>	Clamping shell for pinning, aluminium

## Additional elements

<b>FD C4400</b>	Flat seal
-----------------	-----------