

K-PUR-BREMSSPIRALE

PUR brake coil with connection

HANSA FLEX

Properties

Connection 1 + 2	metric cylindrical outer thread
Standard	tested in accordance with DIN 74323 DIN 74324 ISO 7268-2 ISO 7375-2 DIN 73378 DIN 74310-2
Approval	German Technical Surveyance Association (TÜV)- type approved (Certificate R 9910199)
Temp. min.	-40 °C
Temp. max.	90 °C
Material	PUR



Additional information

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

Item

Identification	G1 + G2	Internal Ø (mm)	External Ø (mm)	Wall thickness (mm)	Length (m)	Colour
K- 07 10 13 21	M 16 x 1.5	8,0	12,0	2,0	4,50	black
K- 07 10 13 22	M 16 x 1.5	8,0	12,0	2,0	4,50	yellow
K- 07 10 13 23	M 16 x 1.5	8,0	12,0	2,0	4,50	red
K- 07 10 13 24	M 16 x 1.5	8,0	12,0	2,0	5,50	black
K- 07 10 13 25	M 16 x 1.5	8,0	12,0	2,0	5,50	yellow
K- 07 10 13 26	M 16 x 1.5	8,0	12,0	2,0	5,50	red