

Properties

Connection 1 + 2 metric cylindrical outer thread

Standard tested in accordance with
 DIN 74323
 DIN 74324
 ISO 7268-2
 ISO 7375-2
 DIN 73378
 DIN 74310-2

Approval German Technical Surveyance Association (TÜV)-
 type upproved (Certificate R 9910199)

Temp. min. -40 °C

Temp. max. 90 °C

Material PUR



Additional information

- will not break at fittings
- excellent antikink characteristics – kinking leaves no defects
- longer operation length
- highly resistant to tearing off at fittings
- excellent springback characteristics
- unplasticized so no embrittlement
- resistant to oil and grease
- resistant to UV and ozon
- service life many times longer than conventional coil tubing

Item

Identification	G1 + G2	Internal Ø (mm)	External Ø (mm)	Wall thickness (mm)	Length (m)	Colour
K-07 10 13 21	M 16 x 1.5	8,0	12,0	2,0	4,50	black
K-07 10 13 22	M 16 x 1.5	8,0	12,0	2,0	4,50	yellow
K-07 10 13 23	M 16 x 1.5	8,0	12,0	2,0	4,50	red
K-07 10 13 24	M 16 x 1.5	8,0	12,0	2,0	5,50	black
K-07 10 13 25	M 16 x 1.5	8,0	12,0	2,0	5,50	yellow
K-07 10 13 26	M 16 x 1.5	8,0	12,0	2,0	5,50	red