

# K-BIMETALLTHERMOMETER 46

Bimetallic thermometers

**HANSA FLEX**

## Properties

Type	46
Display correction	On end of stem
Operating pressure	Max. 6 bar (on thermowell)
Thermowell	Clamped (removable), copper alloy
Housing	Plastic
Inspection glass	Plexiglass



## Note

Further information on request

## Description

Applications: Heating, plumbing, universal.

## Item

Identification	Indicating range	Ø (mm)	stem length	Thread
K- 07 20 09 86	0 °C to +60 °C	63,0	40 mm	G 1/2
K- 07 20 09 87	0 °C to +120 °C	63,0	40 mm	G 1/2
K- 07 20 09 88	0 °C to +60 °C	63,0	60 mm	G 1/2
K- 07 20 09 89	0 °C to +120 °C	63,0	60 mm	G 1/2
K- 07 20 09 90	0 °C to +60 °C	63,0	100 mm	G 1/2
K- 07 20 09 91	0 °C to +120 °C	63,0	100 mm	G 1/2
K- 07 20 10 19	0 °C to +60 °C	80,0	40 mm	G 1/2
K- 07 20 10 20	0 °C to +120 °C	80,0	40 mm	G 1/2
K- 07 20 10 21	0 °C to +60 °C	80,0	60 mm	G 1/2
K- 07 20 10 22	0 °C to +120 °C	80,0	60 mm	G 1/2
K- 07 20 10 23	0 °C to +60 °C	80,0	100 mm	G 1/2
K- 07 20 10 24	0 °C to +120 °C	80,0	100 mm	G 1/2