K-GMM KUNSTOFF UNTEN

Glycerine-filled pressure gauges, connection radial on bottom

Properties

Type	113.13
Design	Glycerine-filled Bourdon-tube pressure gauge
Application	For gaseous or liquid media which do not corrode copper alloy,do not have high viscosity and do not crystallise
Accuracy class	2,5
Media temperature	max. +60 °C
Ambient temperature	-20 °C to +60 °C
Housing	plastic, black
Measuring element and movement	Copper alloy
Inspection glass	PMMA, welded to housing



Note

Further information on request

Description

For measuring points with high dynamic pressure loads and vibrations

Item

Identification	Measuring range	Ø (mm)	Connection
K- 07 20 07 55	-1 / +0.6 bar	63,0	G 1/4"
K- 07 20 07 56	-1 / +1.5 bar	63,0	G 1/4"
K- 07 20 07 57	-1 / +3.0 bar	63,0	G 1/4"
K- 07 20 07 58	-1 / +5.0 bar	63,0	G 1/4"
K- 07 20 07 59	-1 / +9.0 bar	63,0	G 1/4"
K- 07 20 07 60	-1 / 0.0 bar	63,0	G 1/4"
K- 07 20 07 61	0 - 1.0 bar	63,0	G 1/4"
K- 07 20 07 62	0 - 1.6 bar	63,0	G 1/4"
K- 07 20 07 63	0 - 2.5 bar	63,0	G 1/4"

Despite careful checking, we cannot guarantee the accuracy of all information included on this site, and we accept no liability.