K-GMM KUNSTOFF UNTEN

Glycerine-filled pressure gauges, connection radial on bottom



| Properties | | |
|--------------------------------|---|--|
| Туре | 113.13 | |
| Design | Glycerine-filled Bourdon-tube pressure gauge | |
| Application | For gaseous or liquid media which do not corrode copper alloy,do not have high viscosity and do not crystallise | |
| Accuracy class | 2,5 | |
| Media temperature | max. +60 °C | |
| Ambient temperature | -20 °C to +60 °C | |
| Housing | plastic, black | |
| Measuring element and movement | Copper alloy | |
| Inspection glass | PMMA, welded to housing | |



Note

Further information on request

Description

For measuring points with high dynamic pressure loads and vibrations

| Item | | | | |
|----------------|-----------------|-----------|------------|--|
| Identification | Measuring range | Ø (mm) | Connection | |
| K- 07 20 07 55 | -1 / +0.6 bar | 63,0 | G 1/4" | |
| K- 07 20 07 56 | -1 / +1.5 bar | 63,0 | G 1/4" | |
| K- 07 20 07 57 | -1 / +3.0 bar | 63,0 | G 1/4" | |
| K- 07 20 07 58 | -1 / +5.0 bar | 63,0 | G 1/4" | |
| K- 07 20 07 59 | -1 / +9.0 bar | 63,0 | G 1/4" | |
| K- 07 20 07 60 | -1 / 0.0 bar | 63,0 | G 1/4" | |
| K- 07 20 07 61 | 0 - 1.0 bar | 63,0 | G 1/4" | |
| K- 07 20 07 62 | 0 - 1.6 bar | 63,0 | G 1/4" | |
| K- 07 20 07 63 | 0 - 2.5 bar | 63,0 | G 1/4" | |