

K-KFMM U MBAR

Capsule-type pressure gauges, connection radial on bottom

HANSA FLEX

Properties

Type	611.10 (Ø 63), 612.20 (Ø 100)
Design	Capsule-type pressure gauge
Application	For gaseous, dry, non-corrosive media
Accuracy class	1,6
Media temperature	max. +100 °C
Ambient temperature	-20 °C to +60 °C
Housing	Steel, black (Ø 63 mm)CrNi steel (Ø 100 mm)
Measuring element and movement	Copper alloy
Inspection glass	Plexiglass (Ø 63 mm), flat instrument glass (Ø 100 mm)



Note

Further information on request

Description

With zero correction

Item

Identification	Measuring range	Ø (mm)	Connection
K- 07 20 06 88	-160 / 0 mbar	63,0	G 1/4"
K- 07 20 06 89	-100 / 0 mbar	63,0	G 1/4"
K- 07 20 06 90	-60 / 0 mbar	63,0	G 1/4"
K- 07 20 06 91	0 - 40 mbar	63,0	G 1/4"
K- 07 20 06 92	0 - 60 mbar	63,0	G 1/4"
K- 07 20 06 93	0 - 100 mbar	63,0	G 1/4"
K- 07 20 06 94	0 - 160 mbar	63,0	G 1/4"
K- 07 20 06 95	0 - 250 mbar	63,0	G 1/4"
K- 07 20 06 96	0 - 400 mbar	63,0	G 1/4"
K- 07 20 01 13	-160 / 0 mbar	100,0	G 1/2"
K- 07 20 01 14	-100 / 0 mbar	100,0	G 1/2"
K- 07 20 01 15	-60 / 0 mbar	100,0	G 1/2"
K- 07 20 01 16	-25 / +15 mbar	100,0	G 1/2"
K- 07 20 01 17	-40 / +20 mbar	100,0	G 1/2"
K- 07 20 01 18	0 - 25 mbar	100,0	G 1/2"
K- 07 20 01 19	0 - 40 mbar	100,0	G 1/2"
K- 07 20 01 20	0 - 60 mbar	100,0	G 1/2"
K- 07 20 01 21	0 - 100 mbar	100,0	G 1/2"
K- 07 20 01 22	0 - 160 mbar	100,0	G 1/2"
K- 07 20 01 23	0 - 250 mbar	100,0	G 1/2"
K- 07 20 01 24	0 - 400 mbar	100,0	G 1/2"